



Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 8-10-2018 Revision date: 27-7-2021 Supersedes version of: 13-7-2020 Version: 1.6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Putoline Action Fluid (AE)
UFI : X740-D081-9004-3JV4
Product code : PO.20.04
Vaporizer : aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use
Use of the substance/mixture : Solvent-based cleaner

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Putoline Oil
Dollegoorweg 15
7602 EC Almelo - Netherlands
T 0031 (0)546 81 81 65
vib@putoline.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS09

Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.

EUH-statements

: EUH208 - Contains Naphthenic acids, zinc salts, basic. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	(CAS-No.) 64742-49-0 (EC-No.) 927-510-4 (EC Index-No.) 649-328-00-1 (REACH-no) 01-2119475515-33	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Propane substance with a Community workplace exposure limit (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (REACH-no) 01-2119485395-27	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Naphthenic acids, zinc salts, basic	(CAS-No.) 84418-50-8 (EC-No.) 282-762-6 (REACH-no) 01-2119988500-34	0,1 – 1	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
-------------------------------------	---------------------------------------------------------------------------	---------	----------------------------------------------------------------------

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	------------------------------------------------------------------------------------------------------------------------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Butane (106-97-8)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Butane
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA) [1]	1450 mg/m ³
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
WEL STEL (OEL STEL) [ppm]	750 ppm

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Butane (106-97-8)	
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Propane (74-98-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA [ppm]	1000 ppm
Ireland - Occupational Exposure Limits	
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
Notes (IE)	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2020

isobutane (75-28-5)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2020

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:			
Safety glasses			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless to Amber.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: -44,5 °C
Flash point	: -97 °C
Critical temperature	: 365 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 3100 hPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,632 g/cm ³ at 20 °C
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20,5 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 10,9 vol %

9.2. Other information

VOC content : 508,6 g/l

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

LD50 oral rat	> 5840 mg/kg [OECD 401]
LD50 dermal rat	2920 mg/kg [OECD 402]
LC50 Inhalation - Rat	> 23300 mg/m ³ (4h) [OECD 403]

Naphthenic acids, zinc salts, basic (84418-50-8)

LD50 oral rat	4920 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 0,42 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Putoline Action Fluid (AE)	
Vaporizer	aerosol
Viscosity, kinematic	< 20,5 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
LC50 - Fish [1]	> 13,4 mg/l 96h (Oncorhynchus mykiss) [OECD 203]
EC50 - Crustacea [1]	3 mg/l 48h (Daphnia) [OECD 202]
ErC50 algae	10 – 30 mg/l 72h (Pseudokirchneriella subcapitata) [OECD 201]
NOEC chronic fish	1,53 mg/l 28d (Oncorhynchus mykiss) [QSAR Petrotox]
NOEC chronic crustacea	1 mg/l 21d (Daphnia magna) [OECD 211]

Naphthenic acids, zinc salts, basic (84418-50-8)	
LC50 - Fish [1]	≈ 5,62 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	≈ 29,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	≈ 17,7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	≈ 29,9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	≈ 18,1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
Biodegradation	98 % (28d) [OECD 301F]

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 20 01 13* - solvents
HP Code	: HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	Aerosols, flammable (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Transport document description				
UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



14.4. Packing group

Not applicable				
----------------	----------------	----------------	----------------	----------------

14.5. Environmental hazards

Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
-------------------------------------	---------------------------------------------------------------	-------------------------------------	-------------------------------------	-------------------------------------

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content	: 508,6 g/l
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
9.1	Colour	Added	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	-------------------------------------------------------------------------------------------------

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

Putoline Action Fluid (AE)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Naphthenic acids, zinc salts, basic. May produce an allergic reaction.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.